

Wall reading unit A-WR02

Wall reading unit of the off-line hotel system

Our new MACS and TACS offline hotel system wall reader from our ACS-WL product portfolio has been specially developed to accommodate hotel door locks.

This wall reader can directly use the hotel door lock management software and control the electric mortise and magnetic lock with the issued card, thus facilitating the hotel to improve its hotel security management.

It is used in administrative buildings, factories, hotels, apartment houses. Easy to install and operate.



PROPERTIES

- : Hardened plastic panel - resistant, durable
- : Possibility of control - electromagnetic and electric mortise locks
- : Very simple operation
- : Dimensions: 115mm x 75mm x 21mm
- : Working temperature: -10° -70°
- : Storage temperature: -25° -125°
- : Operating humidity: 5% - 95%
- : Output - NO/NC/COM/Wiegand 26
- : Card reading distance - 20~50mm
- : Supports T5557 type cards (TACS), Mifare (MACS)
- : History of passage - up to 2000 records
- : Possibility of connecting an open door sensor
- : Option to link with exit button
- : Suitable for checking access to hotel buildings

SPECIFICATIONS

Voltage source:	12V DC
Actual consumption:	100mA
Time to unlock in sec.	≈ 1.5s
Pass History:	2000 unlock records
Dimensions:	115mm 5mm x 21mm
Card Type:	T5557 (TACS), Mifare (MACS)



www.acssolution.cz

The leader in door opening solution

Updated: 2/2023, ACS Solution s.r.o. Specifications can subject to change without notice Note: The colors of the images in this brochure may differ from the actual colors