

# Wall reading unit A-WR02

## Wall reading unit of the off-line hotel system

Our new MACS and TACS offline hotel system wall reader from our ACS-TTlock product portfolio has been **specially developed** to accommodate hotel door locks.

This wall reader can directly use the **hotel door lock management software** and **control** the electric mortise and magnetic lock with the **issued card**, thus facilitating the hotel to **improve its hotel security management**.

It is used in **administrative buildings, factories, hotels, apartment houses**. Easy to install and operate.



### PROPERTIES

- : Hardened plastic panel - resistant, durable
- : Possibility of control - electromagnetic and electric mortise locks
- : Very simple operation
- : Dimensions: 115mm x 75mm x 21mm
- : Working temperature: -10° -70°
- : Storage temperature: -25° -125°
- : Operating humidity: 5% - 95%
- : Output - NO/NC/COM/Wiegand 26
- : Card reading distance - 20~50mm
- : Supports T5557 type cards (TACS), Mifare (MACS)
- : History of passage - up to 2000 records
- : Possibility of connecting an open door sensor
- : Option to link with exit button
- : Suitable for checking access to hotel buildings

### SPECIFICATIONS

Voltage source:	12V DC
Actual consumption:	100mA
Time to unlock in sec.	≈ 1,5s
Pass History:	2000 unlock records
Dimensions:	115mm 5mm x 21mm
Card Type:	T5557 (TACS), Mifare (MACS)



[www.acssolution.cz](http://www.acssolution.cz)

The leader in door opening solution

Updated: 2/2023, ACS Solution s.r.o. Specifications can subject to change without notice Note: The colors of the images in this brochure may differ from the actual colors